

OVIA™ iTM Slim Series Intelligent Teller Machine



ITM60 series is a new generation cash recycling **Slim ATM** of OVIA™.

It delivers values with its minimized design, efficiency, security, reliability, convenience beyond customer's expectations.



📍 The Industry's Smallest Footprint

- The industry's smallest size
- Compact, modern and minimized design
- Maximizes space utilization
- Minimizes operating / maintenance space

📍 Maximum Reliability

- Stable and high-speed banknotes processing mechanism
- High speed/precision and powerful (cash / check) recognition
- Advanced error prevention and prompt error recovery

📍 Large Capacity

- 11,000 to 13,500 notes
- 1,500 to 3,800 notes of cash cassette capacity
- Up to 6 denominations recycling (with multi-denomination cassette option)
- 3 segment spaces in the large deposit (reject) cassette

📍 Customizable

- Various models and specifications can be selected according to customer needs
- Choice of various service models: card issuing type, bankbook printing type, coin hopper type, video calling with handset etc.



*iTM61 (front service)-Lobby



📍 iTM60 Series Technical Information

*iTM62 (front service)-Cabin

Servicing	iTM60 iTM61 iTM62	Rear Service (TTW) Front Service (Lobby) Front Service (Cabin)
Customer Interface	Display 2nd Display Keyboard Other	15,6" color LCD Touch Screen 8" color LCD Touch Screen (Optional) PCI Certified EPP, 3-DES Flicker on all entry/exit points, Speaker, Audio Jack
Operator Panel	Opr. Display	15.6" color LCD Touch Screen (iTM60 TTW only)
Cash Recycling Module (Slim)		3 recycling cassettes (recycling/dispense 3,500/3,800 notes) Option: Multi-denomination cassettes (recycling up to 6 x 1,500 notes) 1 deposit/retract/reject cassette (1,200+400+400 notes) Maximum transaction volume : 220 notes Cash handling speed : 10 notes/sec
Coin Dispensing Module		3 dispensing hoppers (min 250 coins in each hopper) Maximum transaction volume: 50 coins (mixed)
Printers	Receipt Journal	Thermal printer (80mm, 220 Ø) Electronic journal (Option: Thermal printer 80mm 220 Ø)
Security Features	Camera Safe Lock	Face, Wrist, (Option: Safe) UL291 Level 1 (Option: CEN L, CEN III) Dial lock + Key lock (long key)
Main Control Unit	Industrial PC	Intel Core i5, RAM 8GB, HDD 500G, DVD-ROM(option)
Software		Windows 7 (Windows 10 migration) , CEN/XFS 3.0
Power Supply		200-240VAC (50/60Hz)
Dimensions / Weight (WxDxH, mm) /(Net, kg)	iTM61 iTM60-62	450 x 680 x 1,465 mm / ~375 kg 550 x 710 x 1,900 mm / ~450 kg
Environment	Temperature Humidity	5~40°C (operation) / -20~60°C (storage) 20~80% (operation) / 10~90% (storage)
Other Options		2D Barcode reader, RFID/NFC, Beacon, Biometric readers, UPS EMV Certified Motorized MS/IC with retract capability, Dip card reader Card Issuing Module, Anti-skimming card drive / sensor, Handset

* Specifications are subject to change without notice.